

Product Data Sheet



AC CLEANER FOAMING SPRAY

Product Description:

ASMACO AC cleaner Foaming Spray is effectively eliminates odors at its source caused by bacteria and mildew in the system. Kills fungus and bacteria, removes bad smell causing contamination. It cleans and deodorize auto HVAC system including vents ducts evaporator core and drain pan and leave a clean fresh scent. Non-toxic, bio-degradable, non-corrosive proven safe formulation.

Key Performance Properties:

- 360° angle application.
- Harmless to human body.
- Powerful foam could soak into the interior of the air conditioner, so that it could directly get rid of the dirt, oil stain and other impurities in the air conditioner.
- Contain pleasant lemon fragrance.
- It is possessed of the ability to recover the refrigeration and heating performance for the air conditioner, save power and extend the duration for the air conditioner.
- Forms a bactericidal film on the air conditioner evaporator and air ducts.
- Disinfects the air conditioning system, eliminates musty odors, kills fungi and bacteria.
- Non-toxic, bio-degradable, non-corrosive proven safe formulation.
- Kills fungus and bacteria, removes bad smell causing contamination.
- Easy to use for all types of ventilation and air conditioning systems (heating/ventilation, air conditioning, climate control.

Applications:

Suitable for use of exterior and interior of Air conditioner, HVAC system.

Typical Properties:

Appearance	Foam
Color	white
Odor	Fragrance smell
Density	1.01±0.025 g/cm ³ @20°C
pH value	10±0.25
Inside pressure (m.pa) @ 25 °C	0.5 ± 0.10

Directions:

- Switch off air-conditioning unit and fans.
- Insert the spray probe into the condensate drain
- Spray half of the can's contents (approx. 30 secs), content is sufficient for 2 applications
- Loosened dirt will escape easily via the drain
- Allow to work for at least 10 minutes prior to operation of the air-conditioning system

Restriction:

- Highly flammable product, not to be used on live equipment.
- Do not expose to temperatures exceeding 500C
- Do not spray on naked flame or any incandescent materials.
- Keep out of reach of children.
- Do not pierce or burn even after use.
- It may burn above 50°C



AC CLEANER FOAMING SPRAY

Antibacterial

Cleans & Disinfects

Product Data Sheet



Shelf life:

The shelf life of ASMACO AC Cleaner foaming spray is 2 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

Packaging:

ASMACO AC Cleaner Foaming Spray 500ml (12 pcs)



Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non - Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107
P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE