

Product Data Sheet



ASMACO CARPET TAPE

Product Description:

Asmaco Carpet Tape is a heavy-duty double-sided rubber adhesive tape to stick carpet to a variety of floor surfaces, including tiles, wood, concrete, stone and even bitumen floors with ease. In addition, it can also be used to affix rugs in a fixed place, reducing the risk of trips and accidents as a result.

Key Performance Properties:

- Anti-slip protection on smooth surfaces
- Resistant to oil and water, soft and comfortable to touch
- For both indoor and outdoor use. Also can be used in skateboard, scooter, treadmills, exercise machine etc Suitable for both industrial applications and home use
- High adhesion, It has good performance in viscosity, and It's Self-adhesive
- making it easy and quick to apply without other tools

Applications:

Surface must be dry, clean, and free of dust and dirt as this will help to establish a solid connection. The tape must be applied evenly and not be overstretched, as this will reduce the strength of the bond. Remove the carpet and apply tape from one side of the perimeter to the other, in order to connect all angles; Gently peel the backing and put the carpet onto the tape; Walk over the carpet or run a carpet roller over the entire area, especially the perimeter, to ensure the carpet and tape stick together.

Typical Properties:

PROPERTIES	METRIC	TEST METHOD
Backing Mesh	50 Mesh	-----
Total Thickness	250 Micron	PSTC-133 / ASTM D 3652
Adhesion to Steel	25 N/25mm	PSTC-101 / ASTM D 3330
Tack Rolling Ball	1 cm	PSTC-6 / ASTM D 3121
Tensile Strength	50 N/25mm	PSTC-131 / ASTM D 3759
Service Temperature	-20°C +100°C	-----
Applying Temperature	+10 ~ 40°C	-----

Size: 48 MM X 15 MTR

Storage and Shelf Life:

Product should be stored in a cool, dry area in original packing and to use within 12month of shipment n stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

Packaging:

ASMACO TEMPERATURE GRADE COLOUR MASKING TAPE - Widths & Lengths available based on customer requirements.



ASMACO
CARPET TAPE

Product Data Sheet



Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE

