Product Data Sheet



ASMACO CHAIN LUBE SPRAY

Product Description:

ASMACO CHAIN LUBE SPRAY is a premium quality high performance penetrating oil that penetrates and lubricates all types of moving parts that have become difficult to operate due to increased friction from wear, corrosion or the buildup of sludge and grime. Its special formula does not contain wax, which leaves a sticky residue that can build up inside chain links and the drivetrain. Contains corrosion-inhibitors for optimal chain protection.

Key Performance Properties:

- Rapid deposition of a long-lasting solid lubricant film that greatly reduces friction and wear.
- Rapid penetration into the pores of the metal to free frozen bolts, sticking linkages, and control cable arms.
- Superior rust busting characteristics.
- Formation of a Triple Barrier Shield to protect against rust and other corrosive buildup.
- Formation of a protective film that rejects abrasive particles such as dirt, sand, and salt.
- Formation of a protective shield against moisture.
- Excellent displacement of any moisture buildup.
- Superior extreme pressure and anti -wear properties to increase equipment life and reduce downtime.
- Will not affect any seal materials or coatings.

Applications:

•Metals •Chains & Sprockets • Chain links • O-Ring Chains • Chainsaws • Farm Equipment • Construction Equipment • Heavy Machinery

Typical Properties:	Unit	Specification
Appearance		Clear Liquid
Colors		Water white
Odors		Mild solvents
Specific gravity		0.83 ± 0.05
Pressure in can	Bar	4.5 ± 1

Applications Method:

Shake the can of ASMACO Chain lube spray well. Hold the can upright and apply from a distance of 15-30 cm (6-12 inches) ensuring that the chain is coated thoroughly.

Caution:

- Store under temperature of 50C, keep cool in ventilated and dry place.
- Keep away from the fire hazard and high temperature.
- Do not puncture or set fire to can.
- Keep out of reach of children.
- Eye Irritant: Rinse eyes thoroughly with plenty of water.

Shelf life:

36 months when stored at 20°C / 50% relative humidity out of direct sunlight.

Packaging:

ASMACO Chain Lube Spray 250ml (12 pcs)



CHAIN LUBE SPRAY

Premium Quality

Lubricant

Product Data Sheet




Shipping Limitations: None

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.









SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE

www.anchorallied.com __