

Product Data Sheet



ASMACO PLASTIC SPRAY PAINT

Product Description:

ASMACO PLASTIC SPRAY PAINT is specially designed to renew the appearance of indoor and outdoor plastics. No primer is required. These sprays are ideal for use on polypropylene, polystyrene, resin, PVC, fiberglass, and vinyl plastics such as chairs, garbage bin, tables, and planters. It is suitable for car bumpers, other accessories of automobiles.

Key Performance Properties:

- No sanding or primer required
- Bonds easily most of the plastic PVC, Resin, and many more
- Resistant to temperature changes.
- Excellent weather ability, strong hiding power, fast drying.
- For interior and exterior applications.

Applications:

- Renew the appearance of indoor and outdoor plastic surface.
- Ideal for chair and tables

Direction For Use:

Use outdoors or in a well-ventilated area. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist. Remove all dirt, grease, oil, salt, and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and dry with a clean cloth. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. If mildew is present, wash with a bleach solution, rinse, and let dry. Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface and in motion while spraying. Apply 2 or more light coats a few minutes apart. Maximum adhesion is achieved in 5-7 days.

DRY & RECOAT TIMES: Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20-30 minutes, to handle in 1 hour and fully dry in 24 hours. Apply a second coat within 1 hour or after 48 hours.

CLEAN-UP: When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Cleanup wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING: If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.



**ASMACO
PLASTIC
SPRAY PAINT**

Product Data Sheet



WARNING!

If you scrape, sand, or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop.

- Do not use this product if rain is imminent.
- Do not expose to temperatures exceeding 50°C
- Do not spray on naked flame or any incandescent materials.
- Keep out of reach of children.
- Do not pierce or burn even after use.
- It may burn above 50°C

Typical Properties:

Appearance	Paint in aerosol can
Color	varies
Odor	Solvent
Solid %age	30±5
Density	1.03±0.05 g/cm ³ @20°C
Drying Time Soft dry	10±5 minutes
Drying Time (Hard dry)	< 30 minutes
Complete curing	24 hours
DFT per coat	30± 5 µ
Inside pressure (m.pa) @ 25 °C	0.5 ± 0.10

Storage and Shelf Life:

The shelf life of ASMACO plastic spray paint is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children. Store in cool, dry conditions, between +5°C and 25°C

Packaging:

ASMACO PLASTIC SPRAY PAINT 400 ML - 12 CANS / CTN

Product Data Sheet



Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE