

Product Data Sheet



WELDFIX ALL PURPOSE CLEANER

Product Description:

ASMACO Weldfix All Purpose Cleaner is a cleaner that can be used to degrease, clean and prepare UPVC and CPVC pipes and pipe fittings. This helps to enhance the performance of Weldfix UPVC cement P 917 and Weldfix CPVC cement C 914.

Key Performance Properties:

- Excellent cleansing performance
- Good degreasing performance

Typical Properties:

Appearance	Low viscous liquid
Colour	Clear
Drying Time, min	5 - 10

Usage Instructions:

Before first use of the cleaner, remove the cap from the bottle. Then use the brush in the cap to apply the cleaner.

Cleaning:

The surfaces to be bonded must first be cleaned of heavy dirt. If pipes are to be bonded, follow the instructions given in the Technical Data Sheets of Weldfix UPVC / CPVC cements. Clean the pipe and pipe surface thoroughly using the applicator attached to the cap till the surfaces are clean from dirt, dust, grease, lubricant etc. Allow the surface to dry before carrying out the bonding operation. Bonding operation may be carried out as per the instructions given in Weldfix UPVC / CPVC cement instructions.

Caution:

Asmaco Weldfix® is a solvent based adhesive and all the precaution as applicable to a solvent based product must be necessarily undertaken while handling. Flammable liquid, avoid excessive heat and sparks and do not smoke while applying. Adequate ventilation is to be ensured during adhesive application. Do not inhale vapors. In case of eye contact, flush immediately with plenty of water and seek medical advice. Keep out of the reach of children. Refer MSDS for more details.

Store in a cool dry place away from direct sunlight, direct flame, heat and moisture.

Packaging:

Asmaco Weldfix PVC Cleaner is Available in tin cans of 237 ml, 473 ml and 946 ml in tin containers.



WELDFIX® ALL PURPOSE CLEANER

Product Data Sheet



Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE

