Product Data Sheet



ASMACO BRAKE CLEANER

Product Description:

ASMACO BRAKE CLEANER is a universal cleaner for automotive industry which cleans, degreases, and evaporates without leaving residues. It is used primarily for cleaning surfaces in vehicles and everyday life intended for subsequent processing (gluing, painting, coating, sealants, etc.) Brake Cleaner can be used on brakes (drum and disc brakes, brake pads, brake blocks, cylinders, springs, and bushings), clutches (clutch linings and components) and on engine parts— extends their service life with regular use.

Key Performance Properties:

- It removes Oils and degrease particles.
- Fast evaporating without leaving no residues.
- It extends the service life of the parts.
- Suitable for brake disc and brake pads.

Applications:

Can be applied by flushing, dipping, spraying, and pouring. Large parts and components are best treated with spray or wet with wide brushes, rags, or similar means. It is usually enough to spray the degreaser on dirty surfaces and let it drain. After the solvent has evaporated, the surfaces will be cleaned and degreased. In case of heavy dirt, wipe the surface.

Typical Properties:

Appearance		Free flowing liquid
Colors		Water white
Odors		solvents
Specific gravity		0.77 ± 0.05
Pressure in can	Bar	4.5 ± 1

Instructions:

Contains acetone, aggressive to paint coatings, some plastics, and rubbers. Before use, it is necessary to check its effect on a specific material or coating. If negative effects are detected, these surfaces must be protected to avoid chemical damage.

Restriction:

This product is highly flammable!

The product must not be drained into the sewer!

Measures must be taken against static electricity!

Wear appropriate gloves and protective clothing when working!

Shelf life:

36 months when stored at 20°C / 50% relative humidity out of direct sunlight.

Packaging:

ASMACO BRAKE CLEANER 500ml (12 pcs)



BRAKE CLEANER

Cleans in Seconds

Non chlorinated

Product Data Sheet





Shipping Limitations: None

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107 P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail: info@anchorallied.com.





SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE

www.anchorallied.com _