

# Product Data Sheet



## ASMACO TIRE SHINE SPRAY

### Product Description:

ASMACO TIRE SHINE SPRAY is especially developed for the decoration and shining of vehicle tires. It helps prevent ozone degradation, which can cause drying, cracking and fading of tire.

### Key Performance Properties:

- Extra gloss enhancers for intense shine.
- Conditions, nourishes, and preserves your tires' rich black look.
- Precision applicator provides even results without messy overspray.
- Protects from harmful elements that can cause cracking and fading.
- One step, easy application; no wiping needed.

### Applications:

- Tire shine

### Direction For Use:

- Hold the Tire Shine Aerosol can 15" to 20" away from tire.
- Spray evenly on clean, dry tire.
- Allow product to dry for at least 5 minutes.
- Do not wipe. Any drips or runs will disappear, leaving a brilliant shine.

It's not just about shine! ASMACO TIRE SHINE help prevent ozone degradation, which can cause drying, cracking and fading.

#### For Best Results

Let stand 15 minutes. Repeat application for maximum shine.

### CAUTION :

- Store under temperature of 50°C, keep cool in ventilated and dry place.
- Keep away from the fire hazard and high temperature.
- Do not puncture or set fire to can.
- Keep out of reach of children.
- Eye Irritant: Rinse eyes thoroughly with plenty of water.



ASMACO  
TIRE SHINE  
SPRAY

# Product Data Sheet



## Typical Properties:

Appearance	--	Clear Liquid
Colors	--	Water white
Odors	--	Mild solvents
Specific gravity	--	0.80 ± 0.05
Pressure in can	Bar	5.5 ± 1

## Storage and Shelf Life:

36 months when stored at 20°C / 50% relative humidity out of direct sunlight.

## Packaging:

ASMACO TIRE SHINE SPRAY 500 ML - 12 CANS / CTN

## Shipping Limitations: None

### Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non – Warranty:** Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.  
**ANCHOR ALLIED FACTORY L.L.C.**

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS  
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE  
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE