

Product Data Sheet



ASMACO WHEEL CLEANER

Product Description:

ASMACO WHEEL CLEANER AND POLISH SPRAY is especially used for alloying wheel rim. It is used for the cleaning of dirt, dust, and stains safely as it doesn't contain any material that makes the wheel rim frayed. ASMACO Wheel cleaner & Polish protects your wheel from dirt and deposit and makes the rim shine bright as new.

Key Performance Properties:

- Doesn't include any material that makes wheel rim frayed.
- Using it periodically makes wheel rim bright and brilliant as new, protecting from dirt and deposit.
- Especially use for alloying wheel rim.
- Clean up dirt, stains and filth which were taken from car braking.

Applications:

- Car wheel cleaner
- Spray the wheel rim which cooled off until wet through.
- Permeate within 30 seconds.
- Wash up the rim through by hydraulic giant with high pressure.
- Wipe dried the wheel rim with a clean, soft cloth.
- To get the best effect, wipe with a dry towel or a soft brush.

Typical Properties:

PROPERTIES	SPECIFICATION
Appearance	Liquid in aerosol can
Color	Colorless
Odor	Solvent
Density	0.9719±0.05 g/cm ³ @20°C
Inside pressure (m.pa) @ 25 °C	0.5 ± 0.10

Restriction:

- Should choice the place which makes water evaporate easily to avoid water permeating into the river, rivulet, or lake.
- Avoid contacting eyes or skin for long time. If contact eyes. Unfortunately, please wash the water and go to see a doctor.
- Please don't puncture, wash water, and go to see a doctor.
- Keep out of reach of children.
- Do not pierce or burn even after use.
- It may burn above 50°C.

Shelf life:

The shelf life of ASMACO Wheel cleaner and polish spray is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not be exposed to temperatures exceeding 500C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children. Store in cool, dry conditions, between +5C and 25°C.

Packaging:

ASMACO WHEEL CLEANER 500ml (12 pcs)



**WHEEL
CLEANER**

Shines

Long Lasting

Product Data Sheet



Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE

