

Product Data Sheet



ASMACO ULTRA DEGREASER FOAM SPRAY

Product Description:

ASMACO ULTRA DEGREASER FOAM SPRAY is a highly effective degreaser to clean engines run cooler, look better, and last longer. Its foaming action quickly removes dirt, dust and road grime. Specifically designed for engines with plastic covers, it is safe cleaner on plastics, under-hood rubber and paint.

Key Performance Properties:

- No scrubbing required.
- Effective cleaner with the function of avoiding rust.
- Useful to clean, uneven and accidental surfaces such as oil dirt surface of engine, air compressor and other machine.
- Safe on Engine components.
- Safely removes dirt, grime, oil, and grease.

Applications:

- Cars
- trucks
- Power movers
- Marine
- Tractors
- RVs, ATVs
- Bikes
- Farms, equipment's and many more.

Direction For Use:

Before Application make sure to the below points.

1. The engine must be off and cool.
2. Care must be taken with all underwood wiring and electronic sensors or components. Cover any open carburetor or intake systems openings, cover expose electrical and electronic components (uncovered cracked, frayed wire or engine, computer can cause short circuit.
3. Shake well and apply generously to dry engine, make sure to apply it on all dirty and greasy surfaces, wipe over spray from exterior body surface quickly with wet cloth to avoid dewaxing or streaking paint.
4. Allow foam to soak for 10 to 15 minutes. Use brush to break heavy deposits, grease, and dirt.
5. Rinse all areas with water from top to down. Minimize rinse water in areas that can cause performance problems (electronic and intake).
6. When completed, remove added coverings. Do not start your engine after you have applied ASMACO engine degreaser until the entire engine is properly rinsed. Rinsing is necessary to clean the engine properly and to avoid potential fire hazard.



ASMACO ULTRA DEGREASER FOAM SPRAY

Product Data Sheet



CAUTION :

- Store under temperature of 50°C, keep cool in ventilated and dry place.
- Keep away from the fire hazard and high temperature.
- Do not puncture or set fire to can.
- Keep out of reach of children.
- Eye Irritant: Rinse eyes thoroughly with plenty of water.

Typical Properties:

Appearance	--	Foamy Spray
Colors	--	white
Odors	--	solvents
Specific gravity	--	1 ± 0.05
Pressure in can	Bar	4.5 ± 1

Storage and Shelf Life:

24 months when stored at 20°C / 50% relative humidity out of direct sunlight.

Packaging:

ASMACO ULTRA DEGREASER 500 ML - 12 CANS / CTN

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE