

Product Data Sheet



ECO. GRADE DOUBLE SIDE TISSUE TAPE



ASMACO ECO. GRADE DOUBLE SIDE TISSUE TAPE

Product Description:

DA8005W Double Sided Adhesive Tapes use non-woven tissue as carrier, coated with Rubber Resin adhesive on both sides, and protected with white color double-sided PE coated silicone release paper.

Key Performance Properties:

Self-adhesive, faster application, no pre-plastering required, easy to apply, resists cracking, do no rot, no blisters or bubbles, more environmentally-friendly job. It won't tear, shrink, stretch or bubble, while it hides joints, cracks and holes permanently.

Applications:

Suitable for general bonding, bag sealing, photos sticking, envelop sealing, shopping bag making, fabric / leather laminating, paper and film flying splicing, fabric positioning during computer embroidering, carpet fixing, foam laminating and die-cutting etc.

Product Use:

It is essential that the user evaluate the Asmaco tape product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on the Asmaco Tape.

Surface Preparation:

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease, oil or other contaminants.

Tape Composition:

Facing Composition	Description	Value (English)	Value (Metric)
Double Side Release Paper	PE coated, white Paper	51 lbs / 3000 ft2	85 gsm
Adhesive	Rubber Resin adhesive	21 lbs / 3000 ft2	35 gsm
Carrier	Tissue	8.4 lbs / 3000 ft2	14 gsm

Product Data Sheet



Typical Properties:

PROPERTIES	METRIC	ENGLISH	TEST METHOD
Total Thickness	80 Micron	3.2Mil	PSTC-133 / ASTM D 3652
Adhesion to Steel	12 N/25mm	43.2 z./In.	PSTC-101 / ASTM D 3330
Tack Rolling Ball	15 cm	6 In.	PSTC-6 / ASTM D 3121
Adhesion to Liner	0.5 N/25mm	1.8 Oz./In.	PSTC-101 / ASTM D 3330
Service Temperature	0 ~ +80 °C	+32 ~ +176 °F	-----
Applying Temperature	+10 ~ 40 °C	+50 ~ +105 °F	-----

Packaging:

Cut Roll: 48 / 50mm (2") / 60 / 63mm (2.5") / 72 / 75mm (3") / 96mm / 100mm (4").
Log Roll: 1020/1240mm x 45 / 50m Jumbo Roll: 1020/1240mm x 1000m /1250m

Storage & Shelf Life:

One year when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

Limited Warranty & Limited Remedy:

Your exclusive remedy & Asmaco Tape obligation shall be, at Anchor Allied Factory's option, to replace or repair the product or refund the purchase price of the product.

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107
P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE