Product Data Sheet



ASMACO STICKER & LABEL REMOVER

Product Description:

Special formula with a strong degumming function removes paper labels and residues. Asmaco Sticker & Label Remover is suitable for many surfaces such as glass, metal, wood, foil and plastic. Asmaco Label Remover easily and safely removes adhesive labels, price tags (e. g. incorrect labels), address and product stickers, identification labels, and label residues. It also removes adhesive residues from foil labels such as vignettes on car windshields. Safe on most surfaces. Facilitates clean and easy removal. Reduces the need for scraping. Reduces packing line blocking caused by labels and adhesive build-up Soluble in solvents, insoluble in water.

Key Performance Properties:

- Directly penetrates to the surface and quickly removes labels and dissolves label residues.
- For removing every kind of stickers, tape residues, markers, crayons, lipstick etc. Can be used easily at different fields.
- The best to use for cleaning stubborn sticker residues.
- Safe to use on all nonporous surfaces at automotive industry like metal, paint, bumpers, plastic and glass.
- Quick and easy application
- Has pleasant bubble gum scent.
- Doesn't contain any CFC propellants. Doesn't damage paintwork or plastics and can be applied to larger areas in minimal time.

Applications:

Safe to use on Auto care, home care windows, leather, vinyl, fabric, auto body, painted surfaces, tools, plastic, metal, cardboard and wood.

Direction For Use:

Apply directly onto the label or sticker to be removed. Wipe away any over spray. Leave for 3 minutes, then peel label Wipe away any adhesive residues. May affect some plastics. Always test a small inconspicuous area before general use. Do not use presence of open flame or sparks. Use only in wellventilated areas. Avoid contact with skin and eyes.

- Do not use this product if rain is imminent.
- Do not expose to temperatures exceeding 50°C
- Do not spray on naked flame or any incandescent materials.
- Keep out of reach of children.
- Do not pierce or burn even after use.
- It may burn above 50°C



ASMACO STICKER & LABEL REMOVER

Product Data Sheet



Typical Properties:

Appearance	Clear liquid
Color	Water white
Odour	Solvent
Density	0.744±0.05 g/cm³ @20°C
Inside pressure (m.pa) @ 25 °C	4 ± 1

Storage and Shelf Life:

The shelf life of ASMACO STICKER & LABEL REMOVER is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children. Store in cool, dry conditions, between +5°C and 25°C.

Packaging:

ASMACO STICKER & LABEL REMOVER 450 ML - 12 CANS / CTN

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.







Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107 P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.

SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE

www.anchorallied.com _______ 2