

# Product Data Sheet



## ASMACO DASHBOARD SPRAY

### Product Description:

ASMACO DASHBOARD SPRAY protects, preserves and Beautifies vinyl, leather, plastic, rubber, fiberglass Perspex and wood. Surfaces regain Luster life and color and receive long lasting protection. Treated surfaces will not Attract dust. An excellent spray in order to keep your Dashboard clean.

### Key Performance Properties:

- Helps prevent cracking, fading, discoloration & premature aging
- Enhances your vehicle's deep, rich look & adds beautiful shine
- Cleans away dirt, dust & debris
- Renews & revitalizes vinyl, rubber & plastic

### Applications:

ASMACO DASHBOARD SPRAY is perfect for vinyl, leather, plastic, rubber, Fiberglass, Perspex and wood.

- Dashboards
- Consoles
- Vinyl Seats
- Door panels

### Direction For Use:

Shake the spray can as well for at least 1 minute at every interval of use. Hold the container approximately 25 to 30 cm away from the object. Wait for few minutes between applications of each layer. Spray lightly onto surface or onto a clean cloth. Wipe surface until an even luster is obtained.

### SURFACE PREPARATION:

Remove all dust, grease from the surface to spray

### Typical Properties:

Physical Appearance	Clear Liquid
Color	Water White
Odor	Fragranced
Inside pressure (m.pa) @ 28 °C	0.45 ± 0.10
Health and Safety	Flammable



## ASMACO DASHBOARD SPRAY

# Product Data Sheet



## Storage and Shelf Life:

The shelf life of ASMACO DASHBOARD SPRAY is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 500C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

## Packaging:

ASMACO DASHBOARD SPRAY 450 ML - 12 CANS/CTN

## Shipping Limitations: None

### Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non – Warranty:** Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م  
**ANCHOR ALLIED FACTORY L.L.C.**

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS  
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE  
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE