

Product Data Sheet



ASMACO ALL PURPOSE PIPE LUBRICANT



ASMACO ALL PURPOSE PIPE LUBRICANT

Product Description:

ASMACO ALL PURPOSE PIPE LUBRICANT is milky white, highly viscous, soft paste like water-based product. It is specially designed to lubricate rubber gaskets of pipelines including PVC and Soil pipes. It is ideal for SWR ring-fit, self-fit sewer, drain piping system for low to non-pressure application. It aids in assembly of push on type joints to ensure correct fit .Asmaco All Purpose Pipe Lubricant doesn't support bacterial growth and it will not swell rubber components.

Key Performance Properties:

- Soft paste like easy to apply in wet or dry conditions
- Non-flammable, Non-toxic, Non-corrosive
- Will not harm rubber gasket or plastic pipe
- Safe for potable water system
- Needs no diluents during applications.
- Doesn't promote bacteria growth

Applications:

Push on pipe joints with rubber or synthetic gaskets.

SPECIFICATIONS:

- Appearance & Consistency : Off white uniform paste.

Direction For Use:

Surface preparation : Lubricating surfaces must be dry and clean, especially free from oil, grease, solvents & dust.

Application Guidelines :

- Asmaco Pipe lubricant ia a ready to use.
- Do not dilute or thin .
- Follow guidelines for lubrication and assembly given by pipe, fitting and gasket manufacturers.
- Ensure proper Cleaning from inside and out side of the fittings .

Application Procedure : Lubricate both the fitting surfaces properly. Remove excess material. Clean after usage .

Product Data Sheet



Storage and Shelf Life:

Store in cool dry place, not over 25°C away from direct sun light and source of heat.
Shelf life : One year in tightly sealed containers when not in use

Packaging:

950 ml plastic container.

Safety:

Use relevant PPEs during application. Refer safety data sheet

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107
P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE