

## ASMACO GOLD UNIVERSAL MULTIFOAM (B1) (FIRE RETARDANT)



### ASMACO GOLD UNIVERSAL MULTIFOAM (B1) (FIRE RETARDANT)

#### Product Description:

ASMACO GOLD UNIVERSAL MULTI FOAM B1 is quick setting single component polyurethane foam with fire retardant properties. It meets the extremely stringent requirements of DIN 4102 Part 1 for Construction Materials; Class B1 where fire ratings up to 240 minutes are achievable. Once cured, the foam can be cut, sawn or plastered over after only one hour providing the working temperatures (can and surfaces) are between +5 to +30oC, ideally 20oC. (Tested according to BS 476 part 22)

#### Key Performance Properties:

- High degree of fire rating: slows down the passage of flames and smoke.
- Quick setting - can be cut, sawn or plastered in 1 hour.
- Economical in use – 300% Triple Expanding foam.
- Fills irregular and broad gaps where most conventional fillers would fail.
- Possesses insulating and sound deadening properties.
- Nonflammable propellant.
- Excellent adhesion & filling capacity and high thermal & acoustical insulation valve.
- Excellent mounting capacity and stability.
- Adheres to almost all building materials with the exception of surfaces such as polyethylene, Teflon, silicone and surface contaminated with oils and greases, mold release agents and similar materials.
- Mould proof, water proof, over paintable.
- Quick drying, moisture curing.
- Closed cell structure, resistant to water absorption.
- Cured foam dries rigid and can be trimmed, shaped and sanded.
- Suitable for sealing high volume low moment gaps.
- It does not contain any propellant gases that are harmful to the ozone layer.

#### Applications:

- Fixing and insulation of door and window frames.
- Filling and sealing gaps, joints and cavities.
- Filling of penetrations in walls.
- Insulating electrical outlets and water pipes.

#### Typical Properties:

Curing system	--	Moisture cure
Tack Free time	Minutes	15 Max.
Cutting Time	Minutes	40-50
Complete curing	Hours	24
Foam color	--	Pink

# Product Data Sheet



Density	Kg/m <sup>3</sup>	15 -22
Adhesion Strength	kPa	PVC to PVC 143,Alumimum plates 133
Elongation at break	%	8-20
Shear Strength	kPa	22-50
Compression strength	kPa	35-100 at 10% compression
Water absorption	%	Max. 0.03 volume
Thermal conductivity	35°C W/(m.K)	<0.035
Foam Yield	Liters	35-50
Building Material Class	--	B1 DIN 4102 part 1
Fire Rating	--	Up to 240 min.
Can temperature	°C	Min.-5, Max.+35
Application temperature	°C	+5 to +35
Temperature Resistance	°C	-40 to +90 when cured

## Instructions:

Optimal can temperature is +20 °C. Application (ambient) temperature is between +5 °C to +30 °C. Shake the can well before use. Screw the tube on the valve. Moisturizing the surfaces and the foam improves adhesion and shortens curing time. Hold the can upside down and activate the foam by pressing the valve. When spray please pay attention to the speed. Fill vertical joints from the bottom up when half- filled enough. When fill gaps in ceiling, uncured foam may drop because of gravity, Fresh foam can be cleaned by acetone immediately. Please support properly after filling until foam cure and adhere to the gap. Foam is tack free after about 10 minutes, can be cut after 60 minutes. Use a knife to smooth the cured foam and treated surface with cement, paint or silicone.

## Restrictions:

- Storage above +30 °C and below -5 °C shortens shelf life.
- Should be stored and transported in vertical position.
- Should be kept in room temperature for at least 12 hours before the application.
- Cured foam will discolor if exposed to ultraviolet light.
- Paint or coat the cured foam for best results in outdoor applications.

## Storage and Shelf Life:

12 months when stored at 20°C / 50% relative humidity out of direct sunlight.

## Packaging:

ASMAGO GOLD UNIVERSAL MULTIFOAM B1 (Straw Type & Gun Type) 750 ML - 12 CANS/CTN

## Safety:

Contains Diphenylmethane-4,4'-Diisocyanate. Harmful by inhalation. Irritating to eyes, respiratory system and skin. Do not breathe spray/Vapour. Wear suitable protective clothing and gloves. Use only in well-ventilated areas. Pressurized container. Keep away from direct sunlight and do not expose temperatures over 50 °C. Do not pierce or burn, even after use. Keep away from sources of ignition, no smoking. Keep out of the reach of child.

# Product Data Sheet



## Shipping Limitations: None

### Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non – Warranty:** Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.  
**ANCHOR ALLIED FACTORY L.L.C.**

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS  
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE  
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE