



Product Data Sheet

AURA AIR FRESHENER CLASSY



Product Description :

Dry Based Premium long lasting fragrances Designed to mask and remove unpleasant odours and refresh the air.

Key Performance Properties :

- Designed to mask and remove unpleasant odours and refresh the air
- Available in 9 fragrances
- Mild Aroma, No overpowering odors
- Good fragrance which is long lasting in air
- Good relaxing and healing properties

Applications :

Air freshener for non-food areas in homes and offices to mask un-pleasant odors and refresh the air. It contains chemical reactants which combine with and neutralize odors, plus a separate, mild, aroma ingredient. The product is also suitable for use as general cleaners in welfare areas such as locker rooms, rest rooms, hallways and offices. No overpowering odor

Typical Properties :

Weight per 10 liter	0.80 +/- 0.07
Inside pressure (m.Pa) @ 28°C	0.60 +/- 0.05

Storage and Shelf Life :

36 months when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

Packaging :

Aura Air Freshener Classy 300 MI - 48 CANS / CTN

Fragrance Available : English Lavender, Green Apple, Cool Air, Berry Berry, Jasmine Bloom, Rose Al Taifi



Product Data Sheet

AURA AIR FRESHENER CLASSY



Shipping Limitations : None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty : Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.

All ANCHOR ALLIED FACTORY LLC datasheets are updated on a regular basis. This technical data sheet supersedes all previous editions relevant to this product. It is the user's responsibility to obtain the recent version.



☎ : +971 6 5342091, 📠 : +971 6 5342107, P.O. Box No.: 21152

MFG. OF SILICONE , ACRYLIC & POLYURETHANE SEALANTS, WATER PROOFING COATINGS, SELF - ADHESIVE TAPES, SPRAY PAINTS, CONTACT ADHESIVE, PVC CEMENTS, EPOXY STEEL