

Product Data Sheet



ASMACO FIXATIVE SPRAY UV CLEAR COAT

Product Description:

ASMACO FIXATIVE SPRAY is a UV-Resistant acrylic clear coat. It provides a permanent, protective coating which protects, art, crafts, and valuable against harmful light rays. It is moisture resistant and smudge proof. It is suitable for Photography, Artwork, Painted surfaces, Wood, Metal, Paper Mache, Plastic/Ceramic, Dried silk, Flowers, Paper, Wicker, etc. It will improve artwork and protect photos made off with pencil, water paints, oil paints, pastel, chalk, charcoal, crayon and ink.



ASMACO FIXATIVE SPRAY UV CLEAR COAT

Key Performance Properties:

- Long lasting Protection to pencil, pastel, chalk, charcoal, crayon
- Non fading, none yellowing, weather resistant
- Premium quality, high durable.
- Excellent finish
- Aerosol formulation gives quick, even spray
- CFC Free
- UV Resistant
- Acid-free/archival safe

Applications:

1. Shake the can well before use for at least 2 minutes.
2. Hold the can upright side direction and the distance from the object should be within 10-12 cm.
3. Keep the can motion from side to side so that the coating is deposited evenly
4. Better to apply several thin coating at an interval of minimum 3 to 5 minutes

Direction For Use:

The surface to be painted must be free from grease, dirt, moisture to attain excellent results.

Typical Properties:

Appearance	Clear liquid in Aerosol can
Specific Gravity	0.878 ± 0.08
% NVM	20.00 ± 5.00
Viscosity On Zyh Cup-1, at 28°C	33.00 ± 4 sec
Viscosity On Ford Cup-4 at 28 °C	15.003 ± sec
Inside pressure (m.pa) @ 28 °C	0.40 ± 0.10
Flash Point	7.00 ± 3°C

Product Data Sheet



Drying time (Surface dry)	<15 minutes
Drying time (Hard dry)	Minimum 1hr.
VOC Content	450g/l
Finish	Smooth
Film Hardness/ Marking	Flexible & hard film.
Res. to washing & abrasion	Satisfactory
Res. To heat & humidity	Satisfactory up to 60°C with high humidity.

Storage and Shelf Life:

The shelf life of Fixative Spray is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 500C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

Packaging:

ASMACO FIXATIVE SPRAY- UV CLEAR COAT 400 ML - 6 CANS/CTN, 100 ML - 12 CANS/CTN

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE