

Product Data Sheet



ASMACO SPRAY PAINT

Product Description:

Quick dry Acrylic based spray paint for all Interior and Exterior Applications. The product has good hiding power, coverage and gives protection against corrosion

Key Performance Properties:

- Quick drying, smooth finish.
- Premium quality, high durable.
- Ideal for wood, metals, plastic, automotive and motorcycle, equipment etc.
- Available more than 55 colors including metallic, fluorescent colors.
- Interior and exterior application.
- Non fading, none yellowing, weather resistant.
- High coverage ability without running or excessive thickness
- Excellent finish
- Aerosol formulation gives quick, even spray
- CFC Free

Applications:

Shake vigorously till glass agitator rattle in the can. Hold the container approximately 30 cm away from the object to be painted. Keep the can motion from side to side so that the coating is deposited evenly. Better to apply several thin coating at an interval of min 10minutes. Better to store can at room temperature.

Surface Preparation:

The surface to be painted must be free from grease, dirt, moisture and rust after that treat with IPA to attain excellent results.

Typical Properties:

| | |
|----------------------------------|--|
| Appearance | Colored liquid in Aerosol can |
| Specific Gravity | 0.945 ± 0.08 |
| % NVM | Solid colors(20.00 ± 5.00)&metallic col.(405±) |
| Viscosity On Zyhn Cup-1, at 28°C | 33.00± 4 sec |
| Viscosity On Ford Cup-4 at 28 °C | 15.003± sec |
| Inside pressure (m.pa) @ 28 °C | 0.40 ± 0.10 |
| Flash Point | 7.00 ± 3°C |
| Drying time (Surface dry) | 68- minutes |
| Drying time (Hard dry) | Minimum 1hr. |
| VOC Content | 450g/l |
| Finish | Smooth |
| Film Hardness/ Marking | Flexible & hard film. |



ASMACO SPRAY PAINT

Interior - Exterior

CFC FREE

Product Data Sheet



| | |
|--|---|
| Res. to washing & abrasion | Satisfactory |
| Res. To heat & humidity | Satisfactory up to 60°C with high humidity. |
| Hot water immersion test/ Sealing test | Passes & satisfactory |
| Services Temperature/Heat Resistance | -40 to +170°C |
| Storage Temperature | 0 to +35°C |
| Application Temperature | +10 to +25°C |

Storage and Shelf Life:

The shelf life of ASMACO spray paint is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

Packaging:

ASMACO SPRAY PAINT 400 ML - 12 CANS/CTN

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non - Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE