

Product Data Sheet



ASMACO GOLD PU FOAM (PREMIUM GRADE)



ASMACO GOLD PU FOAM (PREMIUM GRADE)

Product Description:

PREMIUM GRADE PU Foam is a single component, moisture-curing and self expanding aerosol polyurethane foam. It is designed for easy dispensing through the straw gun included with each can. It does not contain any harmful gases like CFC and HCFC which damage the ozone layer.

Key Performance Properties:

- 300% - Triple Expanding Foam.
- Excellent adhesion & filling capacity and high thermal & acoustical insulation value.
- Excellent mounting capacity and stability.
- Adheres to almost all building materials with the exception of surfaces such as polyethylene, Teflon, silicone and surface contaminated with oils and greases, mold release agents and similar materials.
- Mould proof, water proof, over paintable.
- Quick drying, moisture curing
- Closed cell structure, resistant to water absorption
- Cured foam dries rigid and can be trimmed, shaped and sanded.
- Suitable for sealing high volume low moment gaps.
- It does not contain any propellant gases that are harmful to the ozone layer.

Applications:

- Fixing and insulation of door and window frames.
- Filling and sealing gaps, joints and cavities.
- Filling of penetrations in walls.
- Insulating electrical outlets and water pipes.

Typical Properties:

Curing system	--	Moisture cure
Tack Free time	Minutes	15 Max.
Cutting Time	Minutes	45-60
Complete curing	Hours	24
Foam color	--	Light yellow
Density	Kg/m ³	12-25
Fire class of the cured foam	---	B3
Adhesion Strength	kPa	PVC to PVC 143, Aluminum plates 133

Product Data Sheet



Elongation at break	%	8-18
Shear Strength	kPa	25-50
Compression strength	kPa	40100- at 10% compression
Water absorption	%	Max. 0.03 volume
Thermal conductivity	35 ⁰ C W/(m.K)	<0.035
Yield per 100 ml	Liters	6
Can temperature	°C	Min.-5, Max.+35
Application temperature	°C	+5 to +35
Temperature Resistance	°C	-40 to +90 when cured

Instructions:

Optimal can temperature is +20 °C. Application (ambient) temperature is between +5 °C to +30 °C. Shake the can well before use. Screw the tube on the valve. Moisturizing the surfaces and the foam improves adhesion and shortens curing time. Hold the can upside down and activate the foam by pressing the valve. When spray please pay attention to the speed. Fill vertical joints from the bottom up when half-filled enough. When fill gaps in ceiling, uncured foam may drop because of gravity, Fresh foam can be cleaned by acetone immediately. Please support properly after filling until foam cure and adhere to the gap. Foam is tack free after about 10 minutes, can be cut after 60 minutes. Use a knife to smooth the cured foam and treated surface with cement, paint or silicone.

Restrictions:

- Storage above +30 °C and below -5 °C shortens shelf life.
- Should be stored and transported in vertical position.
- Should be kept in room temperature for at least 12 hours before the application.
- Cured foam will discolor if exposed to ultraviolet light.
- Paint or coat the cured foam for best results in outdoor applications.

Storage and Shelf Life:

12 months when stored at 20°C / 50% relative humidity out of direct sunlight.

Packaging:

ASMACO GOLD PU FOAM (PREMIUM GRADE) 500 ML, 750 ML - 12 CANS/CTN

Safety:

Contains Diphenylmethane-4,4'-Diisocyanate. Harmful by inhalation. Irritating to eyes, respiratory system and skin. Do not breathe spray/vapour. Wear suitable protective clothing and gloves. Use only in well-ventilated areas. Pressurized container. Keep away from direct sunlight and do not expose temperatures over 50 °C. Do not pierce or burn, even after use. Keep away from sources of ignition, no smoking. Keep out of the reach of child.

Product Data Sheet



Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107
P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE