

# Product Data Sheet



## ASMACO GLITTER SPRAY

### Product Description:

Glitter spray paint offers an intense sparkling finish for any craft or decorative project. Our Glitter paint also provides a full coverage of radiant shimmer for many surfaces including: wood, metal, wicker, glass, ceramic, pottery, craft foam, paper, plastic and more. Provides full-coverage durability for indoor decorating and home décor.



### ASMACO GLITTER SPRAY

### Key Performance Properties:

- Intense Shimmer Finish
- Multi- Surface Use
- Creates a unique, on-trend glitter finish
- High intensity glitter formula gives a multi-dimensional effect
- Creates a sparkling finish
- Indoor use only
- Ideal for scrapbooking pages
- Buildable glitter paint offers a full, vibrant shimmer with a multi-dimensional look
- Multi surface paint resists stains and scratches, shake well before use to mix glitter pigment
- Interior use on accent pieces, holiday decorations, scrapbook projects and many more
- Formulated to create an intense sparkling finish over a base coat of similar color

### Applications:

- 1.Shake the can well before use for at least 2 minutes.
- 2.Hold the can upright side direction and the distance from the object should be from 20 -30 cm.
- 3.Keep the can motion from side to side so that the coating is deposited evenly
- 4.**After Use:** After each use, clear valve and actuator by holding can upside down and spraying until only clear gas comes out. If spray nozzle becomes clogged, wear eye protection, wipe off the nozzle with lacquer thinner. DO NOT stick pin in spray nozzle opening. Wash hands after use.

### Direction For Use:

The surface to be painted must be free from grease, dirt, moisture to attain excellent results.

### Typical Properties:

Appearance	Colored liquid in Aerosol can
Specific Gravity	0.810 ± 0.08
% NVM	18.00 ± 5.00

# Product Data Sheet



Viscosity On Zyhn Cup-1, at 28°C	38.00± 4 sec
Viscosity On Ford Cup-4 at 28 °C	15.003± sec
Inside pressure (m.pa) @ 28 °C	0.40 ± 0.10
Flash Point	7.00 ± 3°C
Drying time (Surface dry)	< 20 minutes
Drying time (Hard dry)	Minimum 1hr.
VOC Content	450g/l
Finish	Shimmering Finish
Film Hardness/ Marking	Flexible & hard film.
Res. To heat & humidity	Satisfactory up to 60°C with high humidity.

## Storage and Shelf Life:

The shelf life of Fixative Spray is 2 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

## Packaging:

ASMACO GLITTER SPRAY 400 ML - 6 CANS/CTN, 100 ML - 12 CANS/CTN

## Shipping Limitations: None

### Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non – Warranty:** Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.  
**ANCHOR ALLIED FACTORY L.L.C.**

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS  
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE  
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE