



# مصنع انكور الايد ذ.م.م. ANCHOR ALLIED FACTORY L.L.C.

MFG. OF POLYURETHANE, SILICONE & ACRYLIC SEALANTS, SELF-ADHESIVE TAPES SPRAY PAINTS AND HOMECARE PRODUCTS.  
P.O. Box: 21152, Street-17, Industrial Area-15, Sharjah, U.A.E. Tel.: +971-6-5342091, Fax: +971-6-5342107

TRN: 100038453500003

E-mail: info@anchorallied.com  
Website: www.anchorallied.com



## TECHNICAL DATA SHEET

### ASMACO PAINT REMOVER SPRAY

#### 1. DESCRIPTION:

ASMACO PAINT REMOVER SPRAY is especially designed to remover the old paint layers from any substrate. The convenient aerosol can easily spray hard-to-reach areas and will not drip or run.

#### 2. PRODUCT BENEFITS:

- Aggressively strips even the toughest paints.
- No wastage due to accurate spray
- Removes Paint, Varnish, Epoxy, Lacquer, Urethane, Graffiti, Enamel, Shellac, etc...
- Industrial strength.
- Fast acting.
- Water-rinsable.
- Active Formulation removes graffiti. paint over spray & hard to reach areas with ease

#### 3. TYPICAL APPLICATIONS:

- Any metallic surface with mild to heavy paint remains.
- Removes acrylics, epoxies, lacquers, adhesives, and most other automotive finishes.
- Light industrial environments
- Should not be used on fiberglass, plastics, styrene related plastics, vinyl, linoleum.

#### 4. DIRECTION FOR USE:

- Shake can vigorously before and during application.
- Due to the product's powerful stripping action, protect areas that do not require stripping
- Hold can 15 to 20 cm from surface coating to be sprayed
- Allow for the product to work minimum 5 min. for the paint to bubble and blister. (The time may vary depending on the type and thickness of surface coating.)
- Use a spatula and lightly scrape off the residues of paint remained
- A second application may be necessary depending on the type, thickness and age of coating. In case of strong paint residues re-apply the product on the surface till all the old paint is removed.
- Flush surface with water or solvent and allow to dry.

#### 5. TECHNICAL PROPERTIES:

PROPERTIES	SPECIFICATION
Appearance	liquid in aerosol can
Density g/cm <sup>3</sup>	1.23±0.05
Pressure inside in bar@ 25°C	4.0 ±1
Application temperature	25+10°C

#### 6. STORAGE AND SHELF LIFE:

The shelf life of ASMACO PAINT REMOVER SPRAY is 2 years when stored under normal condition of temperature and pressure (10-30°C). Keep away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

**7. PACKING:**

PRODUCT	VOLUME	PACKING
ASMACO PAINT REMOVER SPRAY	400 ML	12 CANS/CTN

*This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.*