

ASMACO STYROFOAM SPRAY PAINT

Product Description:

Asmaco Styrofoam spray paint is a new product line that creates detail while educating, inspiring and driving innovation into schools, clubs, craft and hobby projects!

It is easy to apply and can be used on many kinds of surfaces like Styrofoam, Brand foam, paper, glass, wood, metal, leather, and ABS plastic. It is not suitable for rubber or flexible types of vinyl because it will not dry on these surfaces; it will remain tacky to the touch. It will not adhere to polyethylene or polypropylene. It has super flow and coverage. Asmaco Styrofoam foam spray paint is lead free.

Key Performance Properties:

- Quick drying, smooth finish.
- Premium quality, high durable.
- Ideal for Styrofoam, brand foam wood, metals, plastic, automotive and motorcycle, equipment's etc.
- Interior and exterior application.
- Non fading, none yellowing, weather resistant.
- Super flow and high coverage
- Excellent finish
- Aerosol formulation gives quick, even spray
- CFC Free

Applications:

Shake vigorously till glass agitator rattle in the can. Hold the container approximately 30 cm away from the object to be painted. Keep the can motion from side to side so that the coating is deposited evenly. Better to apply several thin coating at an interval of min 10minutes. Better to store can at room temperature.

Direction For Use:

The surface to be painted must be free from grease, dirt, moisture and rust after that treat with IPA to attain excellent results.

Typical Properties:

Appearance	Colored liquid in Aerosol can
Specific Gravity	0.82 ± 0.08
% NVM	16.00 ± 5.00
Viscosity On Zyhn Cup-1, at 28°C	33.00± 4 sec
Viscosity On Ford Cup-4 at 28 °C	15.003± sec
Inside pressure (m.pa) @ 28 °C	0.40 ± 0.10
Flash Point	7.00 ± 3°C



ASMACO
STYROFOAM
SPRAY PAINT

Product Data Sheet



Drying time (Surface dry)	48- minutes
Drying time (Hard dry)	Minimum 1hr.
VOC Content	380 g/l
Finish	Smooth

Storage and Shelf Life:

The shelf life of ASMACO spray paint is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

Packaging:

ASMACO STYROFOAM SPRAY PAINT 400 ML - 12 CANS/CTN

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE