



مصنع انكور الايد ذ.م.م.

ANCHOR ALLIED FACTORY L.L.C.

MFG. OF SILICONE, ACRYLIC & POLYURETHANE SEALANTS, WATERPROOFING COATINGS, AEROSOL PRODUCTS AND ADHESIVE TAPES
P.O. Box: 21152, Sharjah, U.A.E.
E-mail: info@anchorallied.com

Tel.: +971-6-5342091, Fax: +971-6-5342107

Website: www.anchorallied.com



TECHNICAL DATA SHEET

ASMACO ADHESIVE SPRAY

1. DESCRIPTION:

ASMACO Adhesive spray is a multipurpose aerosol adhesive. It is fast tacking and has a long tack range when applied on both surfaces. It is translucent adhesive for permanently attaching foils, carpeting, many lightweight foams, paper, plastics, cardboard, felt and cloth to painted or unpainted metals, wood, hardboard and other base materials.

2. PROPERTIES:

- Excellent Spray Control
- High solid gives better coverage
- User-friendly Aerosol Can
- Long bonding range
- Fast easy application
- Comes with a lace spray pattern for improved accuracy
- Allows for a bond time of 20 seconds to 30 minutes
- Bonding thin films, foils and fabrics
- Picture framing and scrapbooking
- Ideal for crafts and hobbies

3. TECHNICAL PROPERTIES:

| PROPERTIES | UNIT | SPECIFICATION |
|---------------------|------|-------------------------|
| Product Name | -- | ASMACO ADHESIVE SPRAY |
| Base | -- | Synthetic elastomer |
| Color (wet and dry) | -- | Translucent |
| Specific gravity | -- | 0.813 + 0.05 |
| Inside pressure | m.pa | 0.55 ± 0.1 |
| Spray ability | -- | Lace spray pattern |
| Bonding Rang | -- | 20 second to 30 minutes |
| Solid | %age | 25 |

4. INSTRUCTIONS FOR USE:

Surface Preparation:

Surfaces must be clean, dry and free from dirt, dust, oil, loose paint, wax or grease, etc.

Application Temperature: For best results the temperature of the adhesive and the surfaces being bonded should be at least 65°F (18°C).

Application: Shake the can well before use. Hold can 10-15cm from surface to be sprayed. Make bond while adhesive is aggressively tacky. After use, invert can, depress spray actuator until spray is free of adhesive. Clean spray actuator with mineral sprit.

Bonding Range: 20 Second to 30 minutes.

Extra Strong Bonds: Spray both surfaces and allow a minimum of 30 seconds drying time
Cleanup: Excess adhesive may be removed with mineral sprit.

5. RESTRICTIONS:

- Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas.
- It may burn above 50°C.
- Do not pierce or burn even after use.
- Do not spray on naked flame or any incandescent materials.
- Keep out of reach of children.

6. STORAGE AND SHELF LIFE:

Store product at (16-27°C) for maximum storage life. Higher temperatures reduce normal storage life. Lower temperatures may cause increased viscosity of a temporary nature. Rotate stock on a “first in-first out” basis.

When stored at the recommended conditions in original, unopened container, this product has a shelf life of 18 months from date of manufacture.

7. PACKING:

| PRODUCT | VOLUME | PACKAGE |
|-----------------------|--------|------------|
| ASMACO ADHESIVE SPRAY | 500 ML | 12 PCS/CTN |

This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.