

Product Data Sheet



ASMACO BOND

Product Description:

Asmaco Bond is a two part adhesive, cyanoacrylate and an activator spray in aerosol can that provides quick bonding.

Key Performance Properties:

- Easy to use
- Two part application
- Spray on one substrate and apply adhesive on the other
- Multipurpose
- Rapid curing
- Suitable for porous and uneven substrates
- Strong, durable bond

Applications:

Asmaco Bond is best suited for fixing and repairing wooden parts, bonding MDF, wood, chip board, rubber, most of the plastics, leather, ceramic metals, etc. It is excellent to use in the areas where instant curing of the glue is required.

Typical Properties:

CYANOACRYLATE ADHESIVE	
Appearance	Clear, colourless
Specific gravity	1.05
Viscosity @ 25°C, cPs	1000 - 1800
ACTIVATOR	
Appearance	Colourless to yellowish liquid
Form of packing	Aerosol can

Usage Instructions:

Asmaco Bond is best suited for fixing and repairing wooden parts, bonding MDF, wood, chip board, rubber, most of the plastics, leather, ceramic metals, etc. It is excellent to use in the areas where instant curing of the glue is required. Ensure the surfaces to be bonded are clean and dry. Spray the activator in upright position on to one of the surfaces from about 20 cm distance, apply sufficient quantity of Cyanoacrylate adhesive on the other surface, bring both the surface together and hold for a minimum period of 10 seconds with hand pressure. Give 3 to 5 seconds flash off time after spraying the activator before performing the final bonding. Shake well before use.

Caution:

Asmaco Bond is a two part adhesive and one of them is packed in aerosol can. The precautions as applicable to a aerosol product must be necessarily undertaken while handling. Flammable liquid in pressurized container, avoid excessive heat and sparks and do not smoke while applying. Adequate ventilation is to be ensured during adhesive application. Do not inhale vapors. In case of eye contact, flush immediately with plenty of water and seek medical advice. Keep out of the reach of children. Refer MSDS for more details. Store in a cool dry place, away from direct sunlight, direct flame, heat and moisture.

Storage and Shelf Life:

12 months from the date of manufacturing in original, unopened container. Store upright in cool dry place



ASMACO BOND MDF ADHESIVE KIT

Universal

Fast Adhesive

MDF Kit

Product Data Sheet



Packaging:

Asmaco Bond is Available as two part, 300ml activator in aerosol can and 50ml Caynoacrylate glue in plastic container

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107
P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE

