



# Product Data Sheet

## ASMACO DASHBOARD SPRAY

### Premium Protective Coating for Automotive Dashboards & Interior Surfaces

**Description:** ASMACO DASHBOARD SPRAY is a protective and maintenance spray designed to restore and enhance the appearance of various substrates, including vinyl, leather, plastic, rubber, fiberglass, Perspex, and wood. It helps revive color and luster while providing long-lasting protection. Treated surfaces remain clean and are less prone to attracting dust, making it ideal for maintaining automotive dashboards and interior surfaces.



#### KEY PERFORMANCE PROPERTIES

- Restores & Enhances Appearance
- Provides Long-Lasting Protection
- Revives Color & Luster
- Dust-Repellent Surface
- Easy & Quick Application
- Suitable for Multiple Substrates
- Leaves a Clean, Smooth Finish
- Helps Preserve Surface Condition

#### AREAS OF APPLICATION

ASMACO DASHBOARD SPRAY is suitable for the maintenance and protection of:

- Automotive dashboards and interior trims
- Vinyl surfaces
- Leather surfaces
- Plastic components
- Rubber surfaces
- Fiberglass surfaces
- Perspex surfaces
- Wooden surfaces

#### METHOD OF APPLICATION

**Surface Preparation:** Ensure the surface is clean, dry, and free from dust, dirt, grease, and other contaminants.

**Shake Well:** Shake the can thoroughly before use.

**Application:** Hold the can approximately **15–20 cm** from the surface and spray evenly in a light, uniform coat. Avoid excessive application.

**Spreading:** For best results, spread evenly with a clean, dry microfiber cloth if required.

**Drying:** Allow the treated surface to dry completely before use.

**Reapplication:** Apply a second light coat if required to achieve the desired appearance and protection.

**Note:** Always test on a small, inconspicuous area before full application, particularly on leather, wood, Perspex, or painted surfaces.

#### PACKAGING / SUPPLYING

##### ASMACO DASHBOARD SPRAY

CAN: 450 ml

12 CAN of 450 ml / Carton

#### STORAGE, SHELF LIFE & HANDLING

ASMACO DASHBOARD SPRAY is temperature sensitive and should be stored in a cool, dry, and covered area, protected from direct sunlight, heat sources, and excessive ambient temperatures. Prolonged exposure to elevated temperatures, including storage in shaded but excessively hot areas, may accelerate product ageing, reduce the stated shelf life, and adversely affect application and performance characteristics.

**In hot** climatic conditions, ASMACO DASHBOARD SPRAY must be stored at temperatures below 30°C. Avoid prolonged exposure to extreme temperature fluctuations during storage and transportation.

**When** stored in its original, unopened packaging under the recommended temperature conditions, the product has a shelf life of up to 3 Years from the date of manufacture.

**Stock** should be managed and consumed on a **First-In, First-Out (FIFO)** basis to ensure optimum shelf life and consistent product performance.



# Product Data Sheet

## HEALTH & SAFETY

- Use only in a well-ventilated area and avoid prolonged inhalation of spray mist or vapors.
- Avoid contact with eyes and skin. Wear suitable protective gloves and eye protection during application.
- Keep away from heat, sparks, open flames, and other ignition sources.
- Do not smoke while using the product.
- Do not puncture, burn, or expose the aerosol can to temperatures above 50°C.
- Keep out of reach of children.
- If swallowed, inhaled excessively, or irritation occurs, seek medical attention and refer to the SDS for further information.
- Dispose of the empty container in accordance with local regulations.

## QUALITY & CARE

All products originating from **ANCHOR ALLIED FACTORY LLC** Sharjah, UAE. facility is manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001, ISO 45001 & ISO 50001

## CERTIFICATIONS



## TECHNICAL SPECIFICATIONS

| PROPERTIES              | TYPICAL VALUES | TEST STANDARDS |
|-------------------------|----------------|----------------|
| Color                   | Clear          | —              |
| Appearance              | Liquid         | —              |
| Odor                    | Frananced      | —              |
| Flash Point             | 50°C           | —              |
| Inside pressure at 28°C | 0.45 ±0.10     | MPa            |

### Regional Compliance Notice

Please note that regulatory requirements may vary from one region to another. As a result, product information and recommended applications may differ between countries. For accurate and up-to-date details on product specifications and approved uses, and for any technical guidance, please contact Technical Department of ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE.

### Disclaimer

The technical information, data, and recommendations provided by ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE are supplied in good faith based on current knowledge and experience and are intended for general guidance only. Product performance may vary due to factors beyond ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE 'S control, including materials, substrates, environmental conditions, and methods of application.

Except as expressly agreed in writing, ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE makes no representations or warranties, express or implied, including, without limitation warranties of merchantability or fitness for a particular purpose. To the extent permitted by applicable law, ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE shall not be liable for any loss or damage arising from the use of, or reliance upon the products or this information.

Users are responsible for verifying the product's suitability for the intended application and for conducting appropriate testing under actual project conditions. Product specifications may be amended without prior notice. All sales are subject to ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE current Terms and Conditions of Sale and Delivery. Users must refer to the latest applicable Product Data Sheet prior to use.



**ANCHOR ALLIED FACTORY L.L.C.**

Industrial Area 15 | P.O.BOX, 21152 Sharjah, UAE



+971 6 5342091



+971 6 5342107



www.anchorallied.com



info@anchorallied.com