



Product Data Sheet

ASMACO HELMET CLEANER

Helmet & Protective Gear Cleaner

Description: ASMACO HELMET CLEANER is a foaming cleaning formulation designed to effectively clean and refresh helmet surfaces and internal components. It helps remove dirt, stains, unpleasant odors, and other common contaminants while leaving the cleaned surface fresh and clean. The formulation is designed for convenient application and effective cleaning without leaving excessive residue.



KEY PERFORMANCE PROPERTIES

- Effective foaming action for convenient cleaning.
- Helps remove dirt, dust, stains, and surface contaminants.
- Helps eliminate unpleasant odors and leaves a fresh finish.
- Suitable for cleaning both internal and external helmet surfaces.
- Easy to apply and clean.
- Low-residue formulation when used as directed.
- Helps maintain a clean and fresh appearance of helmet surfaces.
- Formulated for regular cleaning and maintenance.

AREAS OF APPLICATION

- Motorcycle, bicycle, racing, and sports helmets
- Helmet inner liners and padding
- Helmet outer shells and surfaces
- Helmet visors and compatible plastic components
- Safety and protective headgear
- Regular cleaning and maintenance of helmets

Suitable for cleaning internal and external surfaces of various types of helmets and protective headgear, subject to substrate compatibility.

METHOD OF APPLICATION

Preparation

- Shake the can well before use.
- Ensure the helmet is free from loose dirt, dust, and debris.
- Where possible, remove detachable liners, padding, or other washable components before cleaning.
- Check the manufacturer's care instructions and test the product on a small inconspicuous area before full application, particularly on painted, printed, coated, or sensitive surfaces.

Application

- Hold the can approximately **15–20 cm** away from the surface.
- Apply a light and uniform layer of foam onto the area to be cleaned.
- For helmet liners, padding, and fabric surfaces, avoid excessive soaking.
- Allow the foam to remain on the surface for a short period to loosen dirt and contaminants.

Cleaning

- Wipe the treated surface thoroughly using a clean, soft, lint-free cloth or suitable sponge.
- For textured or heavily soiled areas, gently agitate with a soft brush.
- Repeat the application where necessary for stubborn dirt or stains.
- For external helmet surfaces, remove any remaining product with a clean damp cloth.

Drying

- Allow the cleaned helmet and components to dry completely in a well-ventilated area before use.
- Do not expose the helmet to excessive heat or direct flame during drying.
- Ensure internal padding and liners are completely dry before reassembly and use.

Important Precautions

- Do not use on damaged helmet materials or surfaces unless compatibility has been confirmed.
- Avoid direct contact with the eyes and prolonged contact with skin.
- Do not spray directly onto electrical/electronic components, vents, communication equipment, or other sensitive parts.
- Do not use excessive product or saturate helmet padding.
- Always follow the helmet manufacturer's cleaning and maintenance recommendations.



Product Data Sheet

HEALTH & SAFETY

- Use only in a well-ventilated area and avoid prolonged inhalation of spray mist or vapors.
- Avoid contact with eyes and skin. Wear suitable protective gloves and eye protection during application.
- Keep away from heat, sparks, open flames, and other ignition sources.
- Do not smoke while using the product.
- Do not puncture, burn, or expose the aerosol can to temperatures above 50°C.
- Keep out of reach of children.
- If swallowed, inhaled excessively, or irritation occurs, seek medical attention and refer to the SDS for further information.
- Dispose of the empty container in accordance with local regulations.

QUALITY & CARE

All products originating from **ANCHOR ALLIED FACTORY LLC** Sharjah, UAE. facility is manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001, ISO 45001 & ISO 50001

PACKAGING / SUPPLYING

ASMACO HELMET CLEANER

CAN: 250 ml, 12 CAN of 250 ml / Carton

STORAGE, SHELF LIFE & HANDLING

ASMACO HELMET CLEANER is temperature sensitive and should be stored in a cool, dry, and covered area, protected from direct sunlight, heat sources, and excessive ambient temperatures. Prolonged exposure to elevated temperatures, including storage in shaded but excessively hot areas, may accelerate product ageing, reduce the stated shelf life, and adversely affect application and performance characteristics.

In hot climatic conditions, **ASMACO HELMET CLEANER** must be stored at temperatures below 30°C. Avoid prolonged exposure to extreme temperature fluctuations during storage and transportation.

When stored in its original, unopened packaging under the recommended temperature conditions, the product has a shelf life of up to 3 Years from the date of manufacture.

Stock should be managed and consumed on a **First-In, First-Out (FIFO)** basis to ensure optimum shelf life and consistent product performance.

CERTIFICATIONS



TECHNICAL SPECIFICATIONS

PROPERTIES	TYPICAL VALUES	TEST STANDARDS
Color	White	—
Appearance	Foam	—
Odor	Fragrance	—
Density at 25° C	1.01 ± 0.025 g/cm ³	—
Inside pressure at 25°C	10 ± 0.25	bar
pH Value	1.0	G / Sec

Laboratory-controlled test results. All stated values are subject to a tolerance of ±5–10%.



Product Data Sheet

Regional Compliance Notice

Please note that regulatory requirements may vary from one region to another. As a result, product information and recommended applications may differ between countries. For accurate and up-to-date details on product specifications and approved uses, and for any technical guidance, please contact Technical Department of ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE.

Disclaimer

The technical information, data, and recommendations provided by ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE are supplied in good faith based on current knowledge and experience and are intended for general guidance only. Product performance may vary due to factors beyond ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE's control, including materials, substrates, environmental conditions, and methods of application.

Except as expressly agreed in writing, ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE makes no representations or warranties, express or implied, including, without limitation warranties of merchantability or fitness for a particular purpose. To the extent permitted by applicable law, ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE shall not be liable for any loss or damage arising from the use of, or reliance upon the products or this information.

Users are responsible for verifying the product's suitability for the intended application and for conducting appropriate testing under actual project conditions. Product specifications may be amended without prior notice. All sales are subject to ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE current Terms and Conditions of Sale and Delivery. Users must refer to the latest applicable Product Data Sheet prior to use.



ANCHOR ALLIED FACTORY L.L.C.

Industrial Area 15 | P.O.BOX, 21152 Sharjah, UAE



+971 6 5342091



+971 6 5342107



www.anchorallied.com



info@anchorallied.com