

Product Data Sheet



HIGH TEMPERATURE SPRAY PAINT

Product Description:

High Temp Paint has a very good thermal resistance ranging from 400 °C - 600 °C. The paint contains silicon resin along with high quality pigment. Most suitable for chimney, barbecues, engines and motorcycles, furnace, stove oven etc.

Key Performance Properties:

- Quick drying, smooth finish.
- Premium quality, high durable.
- Interior and exterior application.
- Ideal for chimney, barbecues, engines and motorcycles, furnace, stove oven etc.
- Non fading, none yellowing, weather resistant.
- Resistant up to 400 °C- 600 °C.
- High coverage ability without running or excessive thickness
- Excellent finish
- Aerosol formulation gives quick, even spray
- CFC Free

Applications:

Shake the spray can as well for at least 1 minute at every interval of use. Hold the container approximately 25 to 30 cm away from the object to be painted. Wait for few minutes between applications of each layer. For complete harden and adhesion, allow the object to dry for one hour at room temperature. Then heat for 45 to 60 minutes at 180°C

Direction For Use:

Remove all dust, rub off rust, and vanish off grease, after that treat with IPA.

Typical Properties:

	SILVER 400°C	SILVER 600°C	MATT BLACK
Physical Appearance	Colored Liquid	Colored Liquid	Colored Liquid
Color	Silver	Silver	Matt Black
Odor	Solvent	Solvent	Solvent
Resistant to Heat	400 °C	600 °C	400 °C
Flash Point	Not Measurable	Not Measurable	Not Measurable
Surface dry at room temperature	10 – 15 min	10 – 15 min	10 – 15 min
Hard dry	1 Hr	1 Hr	1 Hr
Complete Curing	24 Hr	24 Hr	24 Hr
Health and Safety	Flammable	Flammable	Flammable
Services Temperature	-40 to +170°C	-40 to +170°C	-40 to +170°C



**ASMACO
HIGH TEMP
SPRAY PAINT**

Product Data Sheet



Storage Temperature	0 to +35°C	0 to +35°C	0 to +35°C
Application Temperature	+10 to +25°C	+10 to +25°C	+10 to +25°C

Storage and Shelf Life:

The shelf life of High Temperature spray paint is 2 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 500C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

Packaging:

ASMACO HIGH TEMP SPRAY PAINT 400 ML - 12 CANS/CTN

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE