



Product Data Sheet

ASMACO MONTAGE CLEANER

Heavy-Duty Multipurpose Cleaner & Degreaser for Automotive and Workshop Applications

Description: ASMACO MONTAGE CLEANER is a fast-acting solvent-based cleaner and degreaser designed for the effective removal of dirt, oil, grease, brake fluid, and other petroleum-based and technical residues from suitable automotive and mechanical components. The product helps clean metal parts and tools by dissolving and removing common workshop contaminants, leaving the treated surface clean and free from oily residues. It is suitable for maintenance and cleaning applications in automotive, mechanical, agricultural, and general workshop environments.



KEY PERFORMANCE PROPERTIES

- Fast-acting cleaning and degreasing action.
- Effectively removes oil, grease, dirt, and common workshop contaminants.
- Helps remove brake fluid and other technical fluid residues.
- Suitable for cleaning suitable metal components and tools.
- Helps remove petroleum-based residues without leaving heavy oily deposits.
- Suitable for automotive, mechanical, agricultural, and workshop maintenance applications.
- Easy aerosol application for convenient spot cleaning.
- Suitable for cleaning difficult-to-reach areas and mechanical components.

AREAS OF APPLICATION

ASMACO MONTAGE CLEANER is suitable for cleaning and degreasing:

- Brake components, including brake discs and suitable brake parts.
- Clutch and transmission components.
- Metal mechanical parts and assemblies.
- Workshop tools and equipment.
- Engine and engine-component surfaces.
- Oil filters and suitable filter housings.
- Motorcycle chains and mechanical components.
- Tractor and agricultural machinery components.
- Lawn mower and garden machinery components.
- Door hinges and other mechanical fittings.
- Suitable vehicle bodywork and metal surfaces, subject to substrate compatibility.

METHOD OF APPLICATION

Surface Preparation

- Ensure the component or surface to be cleaned is switched off, cool, and free from loose dirt or debris. Remove heavy deposits mechanically where necessary.

Shake Before Use

- Shake the ASMACO MONTAGE CLEANER aerosol can thoroughly before application.

Application

- Hold the can approximately **15–30 cm** from the surface and spray directly onto the contaminated area. Apply a sufficient amount to wet and dissolve the accumulated oil, grease, dirt, brake fluid, and other technical residues.

Cleaning Action

- Allow the cleaner to act for a short period to dissolve the contamination. For heavily soiled areas, use a suitable clean cloth or brush to assist removal.

Removal of Residues

- Wipe the dissolved contamination with a clean, lint-free cloth. Repeat the application where necessary until the required level of cleanliness is achieved.

Drying

- Allow the cleaned surface to dry completely before returning the component to service. Ensure that no excessive cleaner or dissolved contamination remains on the surface.

Compatibility Check

- Before cleaning painted, coated, plastic, rubber, or other sensitive materials, test the product on a small, inconspicuous area to confirm compatibility.

IMPORTANT APPLICATION PRECAUTIONS

- Use only in a well-ventilated area.
- Do not apply to hot surfaces or running machinery.
- Keep away from flames, sparks, and other sources of ignition.
- Do not smoke during application.
- Avoid prolonged contact with skin and avoid inhalation of spray mist.
- Do not use on electrical or electronic components unless compatibility has been confirmed.
- Do not apply to sensitive surfaces without prior compatibility testing.
- Do not use the product as a lubricant or protective coating.
- Always follow the equipment or vehicle manufacturer's cleaning and maintenance recommendations.



Product Data Sheet

Note: Application rate and cleaning time may vary depending on the type and degree of contamination, surface condition, and ambient conditions. A trial application is recommended where substrate compatibility is uncertain.

EXCLUSION & LIMITATION OF APPLICATIONS

ASMACO MONTAGE CLEANER is intended for cleaning and degreasing of compatible surfaces and components. It is not intended to replace specialized maintenance products, lubricants, protective coatings, or component-specific cleaning systems.

The product should not be used:

- On painted, coated, plastic, rubber, elastomeric, or other sensitive surfaces unless compatibility has been confirmed.
- On electrical or electronic components unless the equipment manufacturer specifically permits the use of solvent-based cleaners.
- On surfaces where solvent exposure may cause swelling, softening, discoloration, cracking, or deterioration.
- As a lubricant or protective coating for mechanical components.
- On hot surfaces, running machinery, or components that may present an ignition hazard.
- Near open flames, sparks, or other sources of ignition.
- For cleaning applications involving food, pharmaceutical, medical, or other regulated products unless specifically approved for such use.
- On components where removal of existing protective coatings, finishes, paints, or surface treatments could adversely affect performance.

Important: Before application, test the product on a small, inconspicuous area to verify compatibility with the substrate and existing surface finish. Always follow the equipment or vehicle manufacturer's recommendations and refer to the applicable SDS for safe handling and use.

QUALITY & CARE

All products originating from **ANCHOR ALLIED FACTORY** LLC Sharjah, UAE. facility is manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001, ISO 45001 & ISO 50001

PACKAGING / SUPPLYING

ASMACO MONTAGE CLEANER

CAN: 500 ml, 12 CAN of 500 ml / Carton

STORAGE, SHELF LIFE & HANDLING

ASMACO MONTAGE CLEANER is temperature sensitive and should be stored in a cool, dry, and covered area, protected from direct sunlight, heat sources, and excessive ambient temperatures.

Prolonged exposure to elevated temperatures, including storage in shaded but excessively hot areas, may accelerate product ageing, reduce the stated shelf life, and adversely affect application and performance characteristics.

In hot climatic conditions, **ASMACO MONTAGE CLEANER** must be stored at temperatures below 30°C. Avoid prolonged exposure to extreme temperature fluctuations during storage and transportation.

When stored in its original, unopened packaging under the recommended temperature conditions, the product has a shelf life of up to 3 Years from the date of manufacture.

Stock should be managed and consumed on a **First-In, First-Out (FIFO)** basis to ensure optimum shelf life and consistent product performance.

HEALTH & SAFETY

- Use only in a well-ventilated area and avoid prolonged inhalation of spray mist or vapors.
- Avoid contact with eyes and skin. Wear suitable protective gloves and eye protection during application.
- Keep away from heat, sparks, open flames, and other ignition sources.
- Do not smoke while using the product.
- Do not puncture, burn, or expose the aerosol can to temperatures above 50°C.
- Keep out of reach of children.
- If swallowed, inhaled excessively, or irritation occurs, seek medical attention and refer to the SDS for further information.
- Dispose of the empty container in accordance with local regulations.



Product Data Sheet

CERTIFICATIONS



TECHNICAL SPECIFICATIONS

PROPERTIES	TYPICAL VALUES	TEST STANDARDS
Color	Clear	—
Appearance	Liquid	—
Odor	Solvent	—
Density at 25° C	0.780 ± 0.05 g/cm ³	—
Inside pressure at 25°C	4.5 ± 1	bar

Laboratory-controlled test results. All stated values are subject to a tolerance of ±5–10%.

Regional Compliance Notice

Please note that regulatory requirements may vary from one region to another. As a result, product information and recommended applications may differ between countries. For accurate and up-to-date details on product specifications and approved uses, and for any technical guidance, please contact Technical Department of ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE.

Disclaimer

The technical information, data, and recommendations provided by ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE are supplied in good faith based on current knowledge and experience and are intended for general guidance only. Product performance may vary due to factors beyond ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE's control, including materials, substrates, environmental conditions, and methods of application. Except as expressly agreed in writing, ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE makes no representations or warranties, express or implied, including, without limitation warranties of merchantability or fitness for a particular purpose. To the extent permitted by applicable law, ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE shall not be liable for any loss or damage arising from the use of, or reliance upon the products or this information. Users are responsible for verifying the product's suitability for the intended application and for conducting appropriate testing under actual project conditions. Product specifications may be amended without prior notice. All sales are subject to ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE current Terms and Conditions of Sale and Delivery. Users must refer to the latest applicable Product Data Sheet prior to use.



ANCHOR ALLIED FACTORY L.L.C.

Industrial Area 15 | P.O.BOX, 21152 Sharjah, UAE



+971 6 5342091



+971 6 5342107



www.anchorallied.com



info@anchorallied.com