



Product Data Sheet

ASMACO TIRE SHINE Professional Alloy Wheel Cleaner

Description: ASMACO TIRE SHINE is a ready-to-use tire care and dressing product designed to restore and enhance the appearance of automotive tires. It provides a clean, fresh and glossy finish while helping maintain the tires' visual appearance. The product is easy to apply and suitable for routine vehicle cleaning and detailing applications.



KEY PERFORMANCE PROPERTIES

- Restores a fresh and attractive appearance to tires.
- Provides a **rich, glossy finish**.
- Enhances the overall appearance of vehicle tires.
- Easy and convenient to apply.
- Suitable for regular tire care and maintenance.
- Helps maintain a clean and well-presented tire appearance.
- Provides uniform coverage when properly applied.
- Suitable for automotive detailing applications.

AREAS OF APPLICATION

ASMACO TIRE SHINE is suitable for use on:

- Passenger vehicle tires.
- SUVs and 4x4 vehicle tires.
- Commercial vehicle and light-truck tires.
- Fleet and transportation vehicles.
- Automotive workshops and service centers.
- Car wash and vehicle detailing facilities.
- Showroom and vehicle presentation applications.

METHOD OF APPLICATION

Surface Preparation.

Ensure the tires are cool and the vehicle is parked on a suitable level surface. Remove loose dirt, mud, dust, and other contaminants from the tire sidewalls using water or a suitable tire cleaner. For heavily soiled tires, clean thoroughly and allow the surface to dry before application.

Shake Well.

Shake the ASMACO TIRE SHINE container thoroughly before use to ensure uniform product consistency.

Application.

Apply ASMACO TIRE SHINE evenly to the clean, dry tire sidewall using a suitable spray applicator, sponge, microfiber applicator, or directly as recommended on the product packaging. Ensure uniform coverage without excessive application.

Spreading.

For an even finish, spread the product uniformly over the tire sidewall using a clean sponge or applicator. Avoid leaving areas with excessive product accumulation.

Dwell / Drying Time.

Allow the product to remain on the tire surface and dry naturally. The required drying time may vary depending on ambient temperature, humidity, and the amount applied.

Excess Product Removal.

If necessary, wipe off any excess product using a clean, dry microfiber cloth to achieve a uniform finish and prevent sling during vehicle operation.

Re-Application.

For tires requiring a higher level of shine or protection, a second light application may be applied after the first coat has dried.

Final Inspection.

Allow the treated surface to dry completely before operating the vehicle. Check the tire sidewalls to ensure a uniform and clean appearance.

IMPORTANT APPLICATION PRECAUTIONS

Apply only to the **tire sidewall**.

- Do not apply to the **tread / tread area**, as this may affect tire traction.
- Do not apply to brake components, brake discs, brake pads, steering components, pedals, or other vehicle control surfaces.
- Do not apply to hot surfaces.
- Avoid application under direct intense sunlight or on excessively hot surfaces.
- Do not allow excessive product accumulation.
- Test on a small inconspicuous area before full application, particularly on non-standard or sensitive surfaces.
- Keep the product away from children and follow the relevant SDS and product-label precautions.

PACKAGING / SUPPLYING

ASMACO TIRE SHINE

CAN: 500 ml

12 CAN of 500 ml / Carton



Product Data Sheet

STORAGE, SHELF LIFE & HANDLING

ASMACO TIRE SHINE is temperature sensitive and should be stored in a cool, dry, and covered area, protected from direct sunlight, heat sources, and excessive ambient temperatures. Prolonged exposure to elevated temperatures, including storage in shaded but excessively hot areas, may accelerate product ageing, reduce the stated shelf life, and adversely affect application and performance characteristics.

In hot climatic conditions, **ASMACO TIRE SHINE** must be stored at temperatures below 30°C. Avoid prolonged exposure to extreme temperature fluctuations during storage and transportation.

When stored in its original, unopened packaging under the recommended temperature conditions, the product has a shelf life of up to 3 Years from the date of manufacture.

Stock should be managed and consumed on a **First-In, First-Out (FIFO)** basis to ensure optimum shelf life and consistent product performance.

QUALITY & CARE

All products originating from **ANCHOR ALLIED FACTORY LLC Sharjah, UAE**. facility is manufactured under a

management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001, ISO 45001 & ISO 50001

HEALTH & SAFETY

- Use only in a well-ventilated area and avoid prolonged inhalation of spray mist or vapors.
- Avoid contact with eyes and skin. Wear suitable protective gloves and eye protection during application.
- Keep away from heat, sparks, open flames, and other ignition sources.
- Do not smoke while using the product.
- Do not puncture, burn, or expose the aerosol can to temperatures above 50°C.
- Keep out of reach of children.
- If swallowed, inhaled excessively, or irritation occurs, seek medical attention and refer to the SDS for further information.
- Dispose of the empty container in accordance with local regulations.

CERTIFICATIONS



TECHNICAL SPECIFICATIONS

PROPERTIES	TYPICAL VALUES	TEST STANDARDS
Color	Clear	—
Appearance	Liquid	—
Odor	Mild Solvent	—
Density at 20° C	0.80 ± 0.05 g/cm ³	—
Inside pressure at 25°C	5.5 ± 1	bar

Regional Compliance Notice

Please note that regulatory requirements may vary from one region to another. As a result, product information and recommended applications may differ between countries. For accurate and up-to-date details on product specifications and approved uses, and for any technical guidance, please contact Technical Department of ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE.

Disclaimer

The technical information, data, and recommendations provided by ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE are supplied in good faith based on current knowledge and experience and are intended for general guidance only. Product performance may vary due to factors beyond ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE's control, including materials, substrates, environmental conditions, and methods of application. Except as expressly agreed in writing, ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE makes no representations or warranties, express or implied, including, without limitation warranties of merchantability or fitness for a particular purpose. To the extent permitted by applicable law, ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE shall not be liable for any loss or damage arising from the use of, or reliance upon the products or this information. Users are responsible for verifying the product's suitability for the intended application and for conducting appropriate testing under actual project conditions. Product specifications may be amended without prior notice. All sales are subject to ANCHOR ALLIED FACTORY L.L.C. SHARJAH, UAE current Terms and Conditions of Sale and Delivery. Users must refer to the latest applicable Product Data Sheet prior to use.



ANCHOR ALLIED FACTORY L.L.C.

Industrial Area 15 | P.O.BOX, 21152 Sharjah, UAE



+971 6 5342091



+971 6 5342107



www.anchorallied.com



info@anchorallied.com