

# Product Data Sheet



## WELDFIX®

### Product Description:

Weldfix® **PVC PRIMER P 918** is a specially formulated solvent for cleaning and preparing the PVC pipes prior to bonding. It removes grease, oil and dirt from PVC pipes. It attacks the PVC surface, allowing a deep penetration of the adhesive which results in a strong permanent joint.

### Key Performance Properties:

- Degreasing and cleaning
- Deep penetration
- Guarantees perfect bonding
- Fast drying formula

### Applications:

- Degreasing, cleaning and preparing PVC pipes for high strength bonding
- Suitable as a thinner for PVC ADHESIVE
- Release joints of PVC pipes through impregnation of the connection joint

#### Instructions for use.

Apply **PVC primer** with the brush on surfaces to be bonded

Clean and degrease surfaces thoroughly and allow drying. Follow with PVC adhesive for a high strength bond.

**It is advisable to perform a suitability test for each application.**



Appearance	Low Viscous Liquid
Colour	Clear / Transparent
Odour	Characteristic
Specific Gravity	0.80 ± 0.02
Application temperature	+ 5 to 35 °C

**Storage :** Products should be stored in a dry and cool place at a temperature of 5<sup>0</sup>-35<sup>0</sup>C, away from sources of ignition. Protect from humidity and direct sunlight.

# Product Data Sheet



## Caution:

Weldfix® P 918 is a solvent based primer and all the precaution as applicable to a solvent based product must be necessarily undertaken while handling. Flammable liquid, avoid excessive heat and sparks and do not smoke while applying. Adequate ventilation is to be ensured during adhesive application. Do not inhale vapors. In case of eye contact, flush immediately with plenty of water and seek medical advice. Keep out of the reach of children. Refer MSDS for more details. Store in a cool dryplace away from direct sunlight, direct flame, heat and moisture.

## Packaging:

Weldfix® is Available in tin cans of 946 ml, 473 ml, 237ml, 118 ml .

## Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non – Warranty:** Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specincations in epect at the time of shipment. mere is no warranty or merchantability Anchor or ntness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. me exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م  
ANCHOR ALLIED FACTORY L.L.C.



Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : [info@anchorallied.com](mailto:info@anchorallied.com).

SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS  
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE  
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE