

Product Data Sheet



ASMACO GRAFFITI SPRAY PAINT

Product Description:

ASMACO graffiti spray paint with its exceptional size and manageability experimental initiative, designed for graffiti, sign painting and high precision general decoration thanks to its low pressure and its valve. Made from acrylic base, with an incredibly fast drying time. Retains its color when exposed to the elements due to the high quality of its components.

Key Performance Properties:

- Low pressure.
- Fast drying.
- Good hardening.
- Excellent flexibility.
- Satin paint
- Strong resistance to scratching once the film is polymerized.
- Does not contain lead nor other heavy metals.
- Good covering capability.
- Durability satin appearance and color
- Easy to apply and repaint.
- Very good resistance to the sun and rain.

Applications:

Due to product, s features we recommended its use for painting all kind of materials, whether it be for decoration, crafts, fine arts and definitely ,anywhere that requires a spray paint of the highest quality.

INSTRUCTION FOR USE:

- 1.Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- 2.Apply to clean, dry surfaces. On rusty metallic surfaces: Remove rust with a wire brush and prepare an anti-rust primer if considered necessary. Apply an anchor layer on plastics and polyesters.
- 3.For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within fifteen minutes with the same paint.
- 4.Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- 5.Never apply to equipment that is plugged in and use in well ventilated areas.
- 6.Request safety datasheets.

Direction For Use:

The surface to be painted must be free from grease, dirt, moisture and rust after that treat with IPA to attain excellent results.



**ASMACO
GRAFFITI
SPRAY PAINT**

Product Data Sheet



Typical Properties:

Appearance	Colored liquid in Aerosol can
Specific Gravity	1.025 ± 0.08
Solid %age	40.00 ± 5.00
Viscosity On Zahn Cup-1, at 25°C	40.00± 4 sec
Viscosity On Ford Cup-4 at 25 °C	15.003± sec
Inside pressure (m.pa) @ 25 °C	0.30 ± 0.10
Drying time (Surface dry)	68- minutes
Drying time (Hard dry)	Minimum 1hr.
VOC Content	450g/l
Finish	Smooth
Film Hardness/ Marking	Flexible & hard film.

Storage and Shelf Life:

The shelf life of ASMACO Graffiti spray paint is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

Packaging:

ASMACO GRAFFITI SPRAY PAINT 400 ML - 12 CANS/CTN

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE