

Product Data Sheet



ASMACO PROTECTION TAPE

Product Description:

PE Film with, pressure sensitive rubber adhesive. Ideal for surface protection of coated and uncoated surfaces from abrasion, smearing or scaling.

Key Performance Properties:

- Low tack and evenly spread adhesive
- Protect against scratch, dirt & damage
- UV Resistant
- Clean release after use
- Able to stand extreme temperature
- Usable on multiple surfaces
- High elongation and tear resistant

Applications:

Widely used for protecting stainless steel sheet, aluminum, Aluminum composite panels, furniture, laminated wooden floor, solid wooden flooring glass, electronic components, screens, and sandwich-panels, UPVC profiles, PVC sheet, AL coil.

Typical Properties:

Color	Black	Black & WHITE	Blue
Total Thickness	60 micron	60 micron	60 micron
Backing	PE Film	PE Film	PE Film
Adhesive	Acrylic	Acrylic	Acrylic
Peel Adhesion	400-600gms/inch	400-600gms/inch	400-600gms/inch
Tensile Strength (ASTM D 3759)*	2.3 N/ Inch	2.3 N/ Inch	2.3 N/ Inch
Max Temperature Resistance	Up to 70°C	Up to 70°C	Up to 70°C

Surface Preparation:


It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

Product Use:

It is essential that the user evaluate the Asmaco tape product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on the Asmaco Tape product between +10 ~ +40°C (+50 ~ +105°F).

Limited Warranty & Limited Remedy:

Your exclusive remedy & Asmaco Tape obligation shall be, at Anchor Allied Factory's option, to replace or repair the product or refund the purchase price of the product.



ASMACO PROTECTION TAPE

UV RESISTANT

LOW TACK

Product Data Sheet



Packaging:

Roll: Width - 1250 mm, Length - 65 YDS / 100 YDS
2 pcs / ctn

Storage & Shelf Life:

Two year when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE