

# Product Data Sheet



## ASMACO TUB & TILE CERAMIC SPRAY PAINT

### Product Description:

Tub & Tile CERAMIC aerosol is a one-step blend of silicone and acrylic spray paint designed to provide excellent adhesion, durability and color retention in high moisture areas. This smooth, glossy, waterproof finish is suitable for use on tiles, sinks and tubs.

### Key Performance Properties:

- Restoration and coating of bath tubs, washbasins, kitchen sinks.
- Quick drying, smooth finish
- Premium quality, high durable.
- Ideal for wood, metals, plastic, automotive and motorcycle, equipment's etc.
- Heat Resistance up to 100°C
- Interior and exterior application.
- Non fading, none yellowing, weather resistant.
- High coverage ability without running or excessive thickness
- Excellent finish
- Aerosol formulation gives quick, even spray
- CFC Free

### Applications:

Shake vigorously till glass agitator rattle in the can. Hold the container approximately 30 cm away from the object to be painted. Keep the can motion from side to side so that the coating is deposited evenly. Better to apply several thin coating at an interval of min 10 minutes. Better to store can at room temperature.

### Direction For Use:

The surface to be painted must be free from grease, dirt, moisture and rust after that treat with IPA to attain excellent results.

**DRY AND RECOAT TIME:** Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 15 minutes, to handle in 1 hour, and can be recoated anytime.

### Typical Properties:

Appearance	White Colored liquid in Aerosol can
Specific Gravity	0.989 ± 0.08
% NVM	(30.00 ± 5.00)
Viscosity On Zahn Cup-1, at 28°C	34.00 ± 4 sec
Viscosity On Ford Cup-4 at 28 °C	15.00 ± 3 sec
Inside pressure (m.pa) @ 28 °C	0.40 ± 0.10
Flash Point	7.00 ± 3°C



## ASMACO TUB & TILE CERAMIC SPRAY PAINT

# Product Data Sheet



Drying time ( Surface dry)	510- Minutes
Drying time (Hard dry)	After 24 Hrs.
VOC Content	454 g/l
Finish	Smooth
Film Hardness/ Marking	Flexible & hard film.
Res. to washing & abrasion	Satisfactory
Res. To heat & humidity	Satisfactory up to 100°C with high humidity.
Hot water immersion test/ Sealing test	Passes & satisfactory

## Storage and Shelf Life:

The shelf life of Tub & Tile Ceramic spray paint is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 500C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

## Packaging:

TUB & TILE CERAMIC SPRAY PAINT 400 ML - 12 CANS/CTN

## Shipping Limitations: None

### Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non – Warranty:** Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م  
**ANCHOR ALLIED FACTORY L.L.C.**

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS  
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE  
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE