

# Product Data Sheet



## ASMACO SELF-ADHESIVE FIBERGLASS MESH TAPE

### Product Description:

Self-Adhesive Fiberglass Mesh Tape, made with 8 x 8 mesh (3.2 x 3.2mm spacing), coated with excellent water-based acrylic adhesive.

### Key Performance Properties:

Self-adhesive, faster application, no pre-plastering required, easy to apply, resists cracking, do not rot, no blisters or bubbles, more environmentally-friendly job. It won't tear, shrink, stretch or bubble, while it hides joints, cracks and holes permanently.

### Applications:

Virtually any commercial or residential application of repairing the cracks and joints or holes of drywall & plasterboard & stucco and the other surface.

### Typical Properties:

Mesh	8 x 8 Threads / Inch (3.2 x 3.2mm Spacing)
Nominal Mass	60 g/m <sup>2</sup>
Adhesive	Water-Based Acrylic Adhesive

### Packaging:

Jumbo Roll: 1.0 x 1000M

Slit Roll: Width - 48mm / 50mm Length - 45M / 50M / 90M / 150M

### Remarks:

1. The data above are typical values only, and should not be used for specifications purpose.
2. Tolerance: Weight and Thickness:  $\pm 10\%$ ; Width:  $\pm 3\text{mm}$ ; Length: Log Roll:  $\pm 0.3\text{m}$ , Jumbo Roll  $\pm 0.5\%$ .
3. The products should be stored at room temperature, kept away from wet and heat source.
4. The users should take test and do trial-application on the above products before coming into application so as to witness and ensure suitability for their special purpose and technique.



ASMACO  
SELF-ADHESIVE  
FIBERGLASS  
MESH TAPE

# Product Data Sheet



## Shipping Limitations: None

### Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non – Warranty:** Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م.  
**ANCHOR ALLIED FACTORY L.L.C.**

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



Management  
System  
ISO 9001:2015  
www.anchorallied.com  
K1 1010000239



الشارقة  
sharjah  
Sharjah Excellence Award



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS  
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE  
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE